



**-47%**  
Energy saving  
TN

**-27%**  
Energy saving  
BT



# FOX

**OSCARTIELLE**  
Cool display

## Fox

	Lunghezza totale Length Longueur Breite Largo Общая длина mm	Lunghezza interno vasca Basin internal length Longueur intérieur bac Innenbreite wanne Longitud interior cuba Длина без выступов mm	Superficie d'esposizione orizzontale Horizontal display surface Surface d'exposition horizontale Gesamte Ausstellfläche Superficie de exposición de arroyo Горизонтальная площадь экспозиции m <sup>2</sup>	Capacità utile Net volume Capacité utile Nutzleistung Capacidad útil Полезный Объем dm <sup>3</sup>	Temperatura d'esercizio Working temperature Temp. de fonctionnement Betriebstemperatur Temp. de ejercicio Рабочая температура °C
BT	100*	1026	0,68	198	-18°C / -23°C [R404]
	150*	1521	1,07	309	
	200	2021	1,46	422	-18°C / -20°C [R290]
	250	2521	1,84	535	
BT/TN	100*	1026	0,68	198	-18°C / -23°C [R404]
	150*	1521	1,07	309	-18°C / -20°C [R290]
	200	2021	1,46	422	(0°C / +2°C)
	250	2521	1,84	535	-18°C / -20°C; (0°C / +2°C)
TN	100*	1026	0,68	198	0°C / +2°C
	150*	1521	1,07	309	
	200	2021	1,46	422	
	250	2521	1,84	535	

Classe climatica ambientale - Environmental climatic class - Classe climatique - Raumklimaklasse - Clase climática ambiental - Климатический класс оборудования: 3 +25 °C 60% U.R. - EN-ISO 23953 - 1/2

\* Disponibile R290 - R290 available